



Manufactures of Self Adhesive Labels and Tags

Standard Matt White Paper with Permanent Adhesive



Photocopier



Laser Printer



Inkjet Printer

A white uncoated paper with a smooth finish giving good printing results with ink-jet & toner systems (Mono & Colour). The material is designed for use on most laser printers & copiers especially mid to high-speed machines.

Face material properties

| | |
|-----------------------|-----------------|
| Grammage | 70 gsm |
| Caliper (thickness) | 90 microns |
| Tensile strength kN/m | 5.2 MD – 2.2 CD |
| Roughness PPS 10 | 5.0 |
| Opacity | 92% |
| Stiffness (Kodak) | - |

Adhesive

A permanent, acrylic based adhesive with good tack & adhesion on a wide range of surfaces. This adhesive also complies with the German BgVV for indirect food contact & short term contact with dry & moist food.

| | |
|----------------------------|----------------|
| Minimum Application Temp | +5°C |
| Storage Range Once Applied | -20°C to +80°C |

Backing

A bleached kraft paper with good lay-flatness & stability

| | |
|-----------------------|-----------------|
| Thickness | 55 microns |
| Grammage | 55 gsm |
| Tensile strength kN/m | 4.8 MD – 1.8 CD |

Environmental

Paper components are either ECF or TCF grade manufactured using pulp from sustainable, managed resources. All dimensions are nominal target specifications, but may vary. All products within our range are manufactured under ISO9001:2008